

## Specification and price

Model		CGK/C-12(L)	CGK/C-18(L)	CGK/C-12(L)	CGK/C-18(L)	CGK/C-28(L)
Power supply	V	220V~240V/50Hz/1ph			380V~415V/50Hz/3ph	
Heating capacity	KW	10.5	18.5	11	20	26
Input power	KW	2.43	4.28	2.5	4.6	6.0
COP		4.32	4.32	4.32	4.32	4.31
Rated current	A	12.3	21.6	4.8	8.8	11.5
<b>Max current</b>	A	16.6	29.2	6.5	11.9	15.5
Max input power	KW	3.3	5.8	3.4	6.3	8.1
Fan motor power	W	90	90	90	90	100
Fan motor quantity	Piece	1	2	1	2	2
Water flow	L/h	2006	3535	2102	3822	4968
Hot water production	L/h	226	398	236	430	559
Refrigerant		R407c				
Water pressure drop	Kpa	≤40	≤50	≤30	≤40	≤45
Net weight	kg	112	164	112	164	190
Gross weight	kg	118	174	118	174	200
Noise	db	52	56	52	56	58
Classification of waterproof		IPX4				
Electric shock proof grade		I				
Pipe size (internal thread)	mm	25	25	25	25	25
Dimension	mm	830*490*1160	1090*480*1260	830*490*1160	1090*480*1260	1256*565*1368
Packing dimension	mm	910*500*1320	1160*500*1410	910*500*1320	1160*500*1410	1310*620*1520
Compressor model/quantity		ZW30KSE*1	ZW52KSE*1	ZW34KSE*1	ZW61KSE*1	ZW79KSE*1

Model		CGK/D-36(L)	CGK/D-52(L)	CGK/D-72(L)	CGK/D-95(L)
Power supply	V	380V~415V/50Hz/3ph			
Heating capacity	KW	40.0	52	72	92
Input power	KW	9.3	12.1	16.7	21.3
COP		4.31	4.31	4.31	4.31
Rated current	A	17.6	22.9	31.7	40.5
<b>Max current</b>	A	23.8	30.9	42.8	54.7
Max input power	KW	12.5	16.3	22.6	28.8
Fan motor power	W	250	350	800	1100
Fan motor quantity	Piece	2	2	2	2
Water flow	L/h	7643	9936	13758	17579
Hot water production	L/h	860	1118	1548	1978
Refrigerant		R407c			R410A
Water pressure drop	Kpa	≤55	≤60	≤62	≤65
Net weight	kg	320	380	482	582
Gross weight	kg	333	400	506	611
Noise	db	65	68	72	75
Classification of waterproof		IPX4			
Electric shock proof grade		I			
Pipe size (internal thread)	mm	32	40	50	65
Dimension	mm	1450*740*1150	1500*800*1515	1850*1000*1950	2000*1100*2080
Packing dimension	mm	1540*820*1320	1580*880*1665	1940*1120*2180	2090*1200*2260
Compressor model/quantity		ZW61KSE*2	ZW79KSE*2	ZW108KSE*2	PSH034*2
<ul style="list-style-type: none"> <li>● Rated working condition: dry-bulb temp: 20℃, wet-bulb temp: 15℃, cool water temp: 15℃, hot water temp: 55℃.</li> <li>● MOQ: 5PCS</li> <li>● Guarantee: 18months from shipped on board date according to bill of lading.</li> <li>● Delivery term: 10-30 working days</li> <li>● Date: Valid time: 15days</li> </ul>					